

Amendments to the Claims:

1. (Currently amended) A method of configuring an image of an object displayed on a display unit of a mobile communication terminal, the method comprising:

in response to a user interacting with a keypad of the mobile communication terminal and without changing the orientation of the keypad, rotating a first image displayed on the display unit, in a first direction relative to the display unit, to display a second image; and

adjusting size, dimension and orientation of the second image relative to dimensions of the display unit,

~~wherein the user input is provided via a keypad of the mobile terminal,~~

wherein the keypad comprises first and second direction keys, wherein the first direction key is associated with a clockwise direction of rotation and the second direction key is associated with a counter-clockwise direction of rotation,

~~wherein pressing the first direction key causes to rotate the first image to be rotated~~ clockwise by approximately 90 degrees,

~~wherein pressing the second direction key causes to rotate the first image to be rotated~~ counter-clockwise by approximately 90 degrees, and

wherein the second image has the same width-height aspect ratio as the first image, and

wherein interacting with the first and second direction keys causes the first image to change orientation such that the second image is same as the first image but displayed in a second orientation and adjusted in size to fit the display unit.

2-6 (Canceled)

7. (Previously amended) The method of claim 1, wherein the keypad further comprises a third direction key, wherein pressing the third direction key causes the first image to be rotated by approximately 180 degrees.

8. (Previously amended) The method of claim 1, wherein the keypad further comprises a fourth direction key, wherein pressing the fourth direction key causes an image displayed on the display unit to be displayed in its original orientation.

9. (Original) The method of claim 1, further comprising:
displaying a soft direction key on the display unit to indicate direction in which the first image is rotated.

10. (Currently amended) The method of claim 1, where in the display unit has a width A and a height B, and the first image has a height C and a width D, wherein the adjusting step comprises:

~~corresponding rotating the first image such that a first edge of the first image having the height C of the first image~~ is aligned approximately in parallel with the width A of the display unit, and

~~corresponding rotating the first image such that a second edge of the first image having the width D of the first image to~~ is aligned approximately in parallel with the height B of the display unit, so such that the second image has is adjusted to have a width [C'] approximately equal to A and a height B.

11. (Cancel)

12. (Currently amended) The method of claim 10, wherein the height [D'] of the second image is adjusted to be approximately equal to $[[D=]] \frac{A^2}{B}$.

13. (Currently amended) The method of claim 10, ~~wherein C=A and D=B, the method~~ further comprising reducing dimensions of the second image proportionally, so that the second image fits within boundaries of the display unit.

14. (Original) The method of claim 9, wherein the soft direction key is displayed when the second image is a rotated representation of the first image.

15. (Original) The method of claim 9, wherein the soft direction key comprises a left soft direction key for representing that the first image is rotated counter-clockwise.

16. (Original) The method of claim 9, wherein the soft direction key comprises a right soft direction key for representing that the first image is rotated clockwise.

17. (Original) The method of claim 15, wherein the left soft direction key flickers.

18. (Original) The method of claim 16, wherein the right soft direction key flickers.

19. (Cancel)

20. (Currently amended) A display apparatus of a mobile communication terminal connected to a fixed non-rotatable keypad having at least one direction key associated with a direction of rotation of a first image displayed on the display apparatus, such that in response to user manipulation of the direction key a second image is displayed on the display apparatus,

wherein the second image is a rotated version of the first image in a first direction relative to the display apparatus,

wherein dimension and orientation of the second image are adjusted in accordance with dimension of the display apparatus,

wherein the keypad comprises first and second direction keys, wherein the first direction key is associated with a clockwise direction of rotation, and the second direction key is associated with a counter-clockwise direction of rotation,

wherein pressing the first direction key causes the first image to be rotated clockwise by approximately 90 degrees,

wherein pressing the second direction key causes the first image to be rotated counter-clockwise by approximately 90 degrees,

wherein the second image has the same width-height aspect ratio as the first image, and

wherein interacting with the first and second direction keys causes the first image to change orientation such that the second image is same as the first image but displayed in a second orientation and adjusted in size to fit the display unit.

21-24 (Cancelled)

25. (Previously amended) The display apparatus of claim 20, wherein the keypad further comprises a third direction key, wherein pressing the third direction key causes the first image to be rotated by approximately 180 degrees.

26. (Original) The display apparatus of claim 25, wherein the keypad further comprises a fourth direction key, wherein pressing the fourth direction key causes the first image to be displayed in its original orientation.

27. (Original) The display apparatus of claim 20, wherein a soft direction key appears on the display unit to indicate direction of rotation of the first image.

28. (Currently amended) The display apparatus of claim 20, ~~where in the display unit has a width A and a height B, and the first image has a height C and a width D, wherein the height C of the first image corresponds with the width A of the display unit, and the width D of the first image corresponds with the height B of the display unit, so that the second image has a~~
width A and a height B where in the display unit has a width A and a height B, and the first image has a height C and a width D, wherein the first image is rotated such that a first edge of the first image is aligned approximately in parallel with the width A of the display unit, and a second edge of the first image is aligned approximately in parallel with the height B of the display unit, such that the second image has a width approximately equal to A.

29. (Cancel)

30. (Currently Amended) The display apparatus of claim 28, wherein the height of the second image is adjusted to be approximately equal to $[[D=]]\frac{A^2}{B}$.

31. (Currently Amended) The display apparatus of claim 28, wherein ~~C=A and D=B~~, such that dimensions of the second image are proportionally reduced, so that the second image fits within boundaries of the display unit.

32. (Original) The display apparatus of claim 27, wherein the soft direction key is displayed when the second image is a rotated representation of the first image.

33. (Original) The display apparatus of claim 32, wherein the soft direction key comprises a left soft direction key for representing that the first image is rotated counter-clockwise.

34. (Original) The display apparatus of claim 32, wherein the soft direction key comprises a right soft direction key for representing that the first image is rotated clockwise.

35. (Original) The display apparatus of claim 33, wherein the left soft direction key flickers.

36. (Original) The display apparatus of claim 34, wherein the right soft direction key flickers.

37. (Canceled)

38. (Previously presented) The method of claim 1, wherein the first direction key is the same as the second direction key.

39. (Previously presented) The method of claim 1, wherein the first and second direction keys are associated with at least one numeric key on the keypad.

40. (Previously presented) The display apparatus of claim 20, wherein the first direction key is the same as the second direction key.

41. (Previously presented) The display apparatus of claim 20, wherein the first and second direction keys are associated with at least one numeric key on the keypad.

42. (Previously presented) The method of claim 1, wherein the keypad further comprises a third direction key, wherein pressing the third direction key causes the second image to be a mirror image of the first image.

43. (Previously presented) The display apparatus of claim 20, wherein the keypad further comprises a third direction key, wherein pressing the third direction key causes the second image to be a mirror image of the first image.

44. (Currently amended) A method for changing orientation and dimension of an image displayed on a display unit of a mobile communication terminal, the method comprising:

in response to a user interacting with a fixed non-rotatable keypad of the mobile communication terminal, changing orientation of a first image displayed on the display unit, relative to the display unit, to display a second image; and

adjusting size and dimensions of the second image relative to dimensions of the display unit,

~~wherein the user input is provided via a keypad of the mobile terminal,~~

wherein the keypad comprises at least one direction key for changing orientation of images displayed on the display unit,

~~wherein interacting with the direction key causes the first image to change orientation of~~ the first image such that the second image is same as the first image but displayed in a second orientation and adjusted in size to fit the display unit.

45. (Previously presented) The method of claim 44, wherein the second image is a rotated version of the first image.

46. (Previously presented) The method of claim 44, wherein the second image is a flipped version of the first image.

47. (Previously presented) The method of claim 44, wherein the second image is a mirror version of the first image.

48. (Previously presented) The method of claim 45, wherein the first image is rotated in a counter-clockwise direction.

49. (Previously presented) The method of claim 45, wherein the first image is rotated in a clockwise direction.

50. (Previously presented) The method of claim 46, wherein the first image is flipped vertically.